MAGELLAN™ 3400VSi

COLATACOCIC



ON-COUNTER HIGH PERFORMANCE BAR CODE READER

The Magellan[™] 3400VSi series of scanners continue the Datalogic tradition of high performance imaging for the high-volume pointof-sale. By duplicating the speed and large field-of-view of laser scanners and expanding the capabilities of imaging, the 3400VSi scanners provide outstanding performance on hard-to-read bar codes and seamless reading of a wide variety of bar codes. This Magellan scanner enables both high speed sweep and presentation scanning techniques, ensuring maximum productivity and ergonomic ease, even with truncated (shortened), out-of-spec or poorly printed codes.

ENHANCING THE CUSTOMER EXPERIENCE

The optional Magellan Customer Service Scanner (CSS) enables retailers to easily engage their customers in mobile commerce programs, allowing them to scan bar codes from mobile phone screens or paper coupons while the cashier continues to scan regular items in parallel, resulting in a significant reduction in total transaction time.

ENTERPRISE FEATURES

Remote Management is supported for OPOS, JavaPOS, Toshiba Remote Management with IBM Systems Director® and Wavelink® Avalanche®. Additional capabilities are available with the Value Added Features included in every Magellan scanner.

FEATURES

- Advanced digital imaging provides class-leading performance and reliability
- Seamless 1D, 2D and Digimarc[®] digital watermark reading
- · Smoothly reads all bar codes, whether displayed on cell phones or printed
- Subtle, adaptive illumination for user comfort
- · Solid-state electronics for silent operation and superior reliability
- Available Magellan Customer Service Scanner (CSS) with omni-mount for reading cell phones, coupons and loyalty cards
- Software driven flexible and upgradeable
- Image capture
- Micro SD card slot
- Multiple interfaces in every unit
- Powered USB auxiliary port
- Checkpoint Systems and Tyco Sensormatic EAS compatible
- Diagnostics reporting
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY - APPLICATION

 Retail: Point of Sale, Mobile Marketing Capabilities, Age Verification, 2D Bar Codes





MAGELLAN™ 3400VSi TECHNICAL SPECIFICATIONS

DECODING CAPABILITY

| DECUDING CAPADI | |
|-----------------------------------|--|
| 1D / Linear Codes | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| 2D Codes | Aztec Code, Data Matrix, QR Code |
| Postal Codes | Australian Post; British Post; Canadian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post |
| Stacked Codes | 6S1 DataBar Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; Micro PDF417, PDF417 |
| Digital Watermarks | Optional support for Digimarc® Barcodes / GS1 DW Code |
| ELECTRICAL | |
| Power Requirements | AC Input: 100-240 VAC, 50-60 Hz DC Input: 5-12 V |
| Power Consumption | Operating (Maximum): 3.8 Watts; Operating (Nominal): 3.6 Watts Sleep Mode: 3.0 Watts |
| ENVIRONMENTAL | |
| Ambient Light | 0 to 86,100 lux |
| ESD Protection (Air Discharge) | 25 kV |
| Humidity (Non-Condensing) | 5 - 95% |
| Particulate and Water Sealing | IP52 |
| Temperature | Operating: 0 to 40 °C / 32 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F |
| INTERFACES | |
| Interfaces | OEM (IBM) USB; RS-232; USB Keyboard, USB Com |
| Auxiliary Ports | Powered Type A USB (USB Com) |
| PHYSICAL CHARAC | TERISTICS |
| Dimensions | Magellan Model 3450VSi: 13.7 x 15.2 x 9.4 cm / 5.4 x 6.0 x 3.7 in |
| Weight | 0.6 kg /1.3 lb |
| | |

| READING PERFORMANCE | |
|-----------------------------------|--|
| Image Capture | Graphic Formats: BMP, JPEG |
| Image Sensor | 1280 x 1024 |
| Light Source | Multiple diffused LEDs, orientation and wavelength optimized for eye comfort |
| Print Contrast Ratio (Minimum) | 25% |
| Read Height | 14.0 cm / 5.5 in |
| Read Rate (Maximum) | 39 Million pixels per second |
| Reading Angle | Pitch: +/- 65°; Roll (Tilt): 0 - 360°; Skew (Yaw): +/- 75° |
| Reading Indicators | Audio speaker with adjustable tone and volume, supports .wav files; Good Read LED; Good Transmission |
| Resolution (Maximum) | 5 mil |
| READING RANGES | |
| Typical Depth of Field | Printing resolution, symbol length, scan angle, contrast and ambient light dependent. 1D / Linear Codes 5 mils: 3.8 to 8.1 cm / 1.5 to 3.2 in 7.5 mils: 1.3 to 11.4 cm / 0.5 to 4.5 in 10 mils: 0 to 15.2 cm / 0 to 6.0 in 13 mils: 0 to 20.3 cm / 0 to 8.0 in 2D Codes 6.6 mils: PDF: 3.8 to 10.2 cm / 1.5 to 4.0 in 10 mils: PDF: 0 to 12.7 cm / 0 to 5.0 in 10 mils: Data Matrix: 1.3 to 6.4 cm / 0.5 to 2.5 in 20 mils: Data Matrix: 0 to 18.0 cm / 0 to 7.0 in |
| SAFETY & REGULATORY | |
| Agency Approvals | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| Environmental Compliance | Complies to China RoHS; Complies to EU RoHS |
| LED Classification | EN62471 and IEC62471 Lamp Illumination Exempt Group |
| UTILITIES | |
| Scanalyzer | Magellan Scanalyzer configuration software is available for download at www.datalogic.com. |
| OPOS / JavaPOS | OPOS and JavaPOS utilities are available for download at no charge. |
| WARRANTY | |
| Warranty | 3-Year Factory Warranty |

ACCESSORIES

Mounts/Stands

90ACC0299 Table/Wall Mount 90ACC0323 Tilt / Riser Mount



© 2017-2019 Datalogic S.p.A and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A and/or its affiliates, registered in the U.S. and the E.U. • Magellan is a trademark of Datalogic S.p.A and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Scanalyzer is a trademark of Datalogic S.p.A and/or its affiliates, registered in many countries, including the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Datalogic S.p.A and/or its affiliates, registered in the U.S. + Digimarc is a trademark of Digimarc is a trademark