

PowerScan® 7000

Industrial Strength Imaging Scanner



Features:

- Solid state design makes the PowerScan 7000 the most rugged and reliable scanner on the market
- Lowest priced full performance industrial handheld scanner on the market
- Best dust and water sealing (IP65) on the market
- Industry leading standard range depth of field (DOF)
- Full multi-interface capability
- Industry Leading Four Year Warranty

Accessories

- Universal Kit
- Scan Stand
- Take Up Reel
- Holster/Fork Lift Mount
- Power Hood

Mechanical

Dimensions

Height: 190 mm / 7.5"

Width: 75 mm / 3.0"

Length: 115 mm / 4.5"

Weight: 312 g / 11 oz (without cable)

Beeper/Speaker: 87 dBA for operator @ 50 cm (typical)

Environmental

Temperature Rating

Operating: -30 to 50°C / -22°F to 122°F

Storage: -40 to 60°C / -40°F to 140°F

Humidity: 5 to 95% NC

Shock: Withstands 50 drops from 6.5' / 2 m to concrete

Vibration: Meets MIL-STD-810E

Water & Particulate Sealing: IP65

Optical

Scanning Width: 2" wide at 1" from scanner; 6" wide at 7" from scanner

Minimum Resolution: 4 mil minimum element size

Skew (Yaw): ± 60°

Pitch: ± 65°

Roll: ± 40°

Ambient light capability: Up to 40,000 Lux

Depth of Field: See Depth of Field Table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	STANDARD RANGE
5 mil	76 to 15.2 cm / 3 to 6"
75 mil	51 to 40.6 cm / 2 to 16"
10 mil	3.8 to 55.9 cm / 15 to 22"
13 mil	2.5 to 76.2 cm / 1 to 30"
20 mil	2.5 to 106.7 cm / 1 to 42"
55 mil	51 to 203.2 cm / 2 to 80"
Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, ambient light, temperature, and scan angle dependant.	

Data Sheet

Electrical

Input Voltage: +4 to 14 VDC

Input Power (typical)

Operating (idling with no trigger): 1.48 W

Standby (idling with no trigger): 0.96 W

Input Current (typical)

Operating (scanning): 295 mA @ 5 VDC

Standby (idling with no trigger): 190 mA @ 5 VDC

Sleep: 1 mA @ 5V

Decoding Capability (autodiscriminates among)

- Codabar
- Code 93
- Code 128
- Code 128 add-ons
- Code 128 ISBT
- EAN 128
- MSI/Plessey
- Standard 2 of 5
- UPC/EAN/JAN
- PDF-417
- Italian Pharmacode 39
- P2 /P5 add-ons
- RSS-14
- RSS Expanded
- Interleaved 2 of 5

Host Communications

RS-232, Keyboard Wedge, USB, Wand Emulation, IBM 46XX, and USB (IBM SurePos).

In addition to standard PC/AT/PS/2, the keyboard wedge interface supports the following: Wyse 55, 60, 120, 150, etc.; IBM 347X/3487/31XX; Digital VT220, 240, 320, 420, 510, 520; Sun 420, ITX, and Sparc 5/10.

Safety & Regulatory

Electrical: Complies to GostR; UL; cUL; EN60950

Emissions: Complies to FCC; EN 55022; CISPR22; VCCI

Laser Classification: CDRH Class II,

(Caution: Laser Radiation - do not stare into beam); IEC 60825 Class 2



PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

PSC Barcode Limited (UK Office)

Axis 3, Rhodes Way,

Watford, England WD24 4TR7

Tel: 44 0 1923 809500

Fax: 44 0 1923 809505

www.psc.com



Copyright © PSC Inc. 2006. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. PSC, the PSC logo, and PowerScan are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.



R40-0135-UK US-C 0106

