



ZT510™  
Industrial Printer

## ZT510 vs. 105SLPlus Comparison Guide

Building on the legacy of its industry-leading 105SLPlus predecessor, the ZT510 strikes the ideal balance between exceptional performance and budget-friendly value. It provides the outstanding durability and reliability you expect from a Zebra printer, plus next-generation printing capabilities, advanced management and monitoring, and future-ready adaptability to power through every challenge in the years to come. Below is an overview of the ZT510's advantages.

### User-Friendly Design

- Customizable, backlit, multi-line display including an intuitive menu, easy-to-use keypad and password protection
- Fast processing for quick throughput of even complex formats and graphic-based labels
- Dynamic QR codes that link to error-specific help videos

### Future-Ready Adaptability

- Flexible design that allows hardware updates in the field, including cutter and peeler
- Two open communication slots to easily add connectivity options, including 802.11a/c, Parallel, IPv6\* and USB Host

### Printer Integration and Management

- Cloud-accessible Link-OS® Printer Profile Manager Enterprise to manage routing, firmware and more, on-site or remotely
- Mobile Device Management connectors to integrate networked printers into AirWatch or SOTI Device Management systems
- Operational Visibility Services (OVS) & Asset Visibility Services (AVS) for real-time insight into printer status, utilization and functionality
- Near Field Communication (NFC), used with the Link-OS Print Touch app, that allows users to pair Android devices

## Printer Comparison\*\*



| Features                                   | ZT510™  |            | 105SLPlus™  |            |
|--|---|------------|---|------------|
| <b>Maximum Print Speed</b><br>(per second) | 203 dpi   | 12"/305 mm | 203 dpi   | 12"/305 mm |
|  | 300 dpi   | 10"/254 mm | 300 dpi   | 10"/254 mm |
| <b>Maximum Print Width</b>                 | 4.09"/104 mm  |            | 4.09"/104 mm  |            |
| <b>Standard Connectivity</b>               | <ul style="list-style-type: none"> <li>• Serial</li> <li>• USB</li> <li>• Gigabit Ethernet</li> <li>• Bluetooth® LE</li> </ul>            |            | <ul style="list-style-type: none"> <li>• Serial</li> <li>• USB</li> <li>• Ethernet</li> <li>• Parallel</li> </ul> |            |
| <b>Optional Connectivity</b>               | <ul style="list-style-type: none"> <li>• Parallel</li> <li>• 802.11a/c with Bluetooth® 4.0</li> <li>• IPv6</li> <li>• USB Host</li> </ul> |            | <ul style="list-style-type: none"> <li>• ZebraNet 802.11b/g Print Server</li> </ul>                               |            |
| <b>Standard RAM</b>                        | 512 MB  |            | 16 MB   |            |
| <b>Standard Flash</b>                      | 2 GB  |            | 8 MB  |            |
| <b>User Interface</b>                      | <ul style="list-style-type: none"> <li>• Backlit, monochrome graphical LCD</li> </ul>   |            | <ul style="list-style-type: none"> <li>• Backlit, monochrome graphical LCD</li> </ul>                             |            |
| <b>Link-OS™ Enabled</b>                    | Yes   |            | No  |            |
| <b>User Setup and Maintenance</b>          | <ul style="list-style-type: none"> <li>• Print Touch</li> <li>• Dynamic QR Codes</li> </ul>   |            | None  |            |



**NA and Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
contact.apac@zebra.com

**EMEA Headquarters**  
zebra.com/locations  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
la.contactme@zebra.com